Street Trees (Per UDO 18.30.130.G) Required: 1 tree / 40' street frontage

Provided: North Private Street (443') = 11 trees Lennox Street (217') = 5 trees

Screening (Per UDO 18.30.130.I)

Required: All exterior-mounted equipment and trash screened from public view Provided: As required

Nonresidential Landscaping (Per UDO 18.30.130.L)

Applicability: Within the front and corner side yards where a street separates a nonresidential use from property zoned or designated on the Comprehensive Plan Map for residential use

Required: 15' width; 1 shade or evg tree / 30' street frontage + 1 ornamental / 3 trees Provided: Lennox Street (217') = 7 shade/evergreen trees + 3 ornamentals; 15' buffer

Applicability: Where a street separates a nonresidential use from property zoned or designated on the Comprehensive Plan Map for nonresidential use Required: 10' width; 1 shade or evg tree / 50' street frontage + 1 ornamental / 3 trees Provided: North Private Street (443') = 9 shade/evergreen trees + 3 ornamentals; 10' buffer

Parking & Vehicular Use Areas; Perimeter (Per UDO 18.30.130.M.2) Required: cont. shrub hedge min. 3' ht. adj. to ROW

Provided: cont. shrub hedge

Parking & Vehicular Use Areas; Interior (Per UDO 18.30.130.M.3) Required: 1 island / 20 parking spaces: 1 shade tree / island; landscape aisles & strips min. 10' width (20' width with pedestrian walkway); 1 tree / 30' landscape aisle/strip Provided: 156 parking spaces = 8 parking islands + 8 trees

Building Facade/Foundation Landscaping (Per UDO 18.30.130.0) Applicability: Nonresidential developments. Does not apply to building facades abutting a sidewalk or the rear yard. Building facades adjacent to public ROW or a parking lot. Required: Landscape area equivalent to 25% building facade with 75% plant coverage: shrubs must be 3' ht.; deciduous & ornamental trees incorporated where appropriate. Planting areas must have a minimum width of either six (6) feet or the equivalent of twenty (20) percent of the building façade height as measured from the ground elevation to the top of the wall or parapet, whichever is greater. Provided: As required

CONCEPT PLANT SCHEDULE



2.5" Cal. B&B

Caltie posidentalie "Prairie Sentinal" / Prairie Sentinal Hackhan Ginkgo biloba 'Princeton Sentry' / Princeton Sentry Ginkgo Nyssa sylvatica 'Wildfire' / Black Gum Platanus x acerifolia / London Plane Tree Quercus bicolor / Swamp White Oak Quercus robur 'Regal Prince' / Regal Prince English Oak Quercus robur x alba 'Crimschmidt' TM / Crimson Spire Oak Zelkova serrata 'City Sprite' TM / City Sprite Zelkova

ORNAMENTAL TREE 1.5" Cal. B&B

Cercis canadensis `Forest Pansy` TM / Forest Pansy Redbuc Malus x 'Spring Snow' / Spring Snow Crab Apple

EVERGREEN TREE 6-8' Ht. Min. B&B Juniperus virginiana "Hillspire" / Hillspire Juniper

Picea glauca 'Densata' / Black Hills Spruce Picea pungens 'Fat Albert' / Colorado Spruce Pinus flexilis 'Vanderwolf's Pyramid' / Vanderwolf's Pyramid Pine

SHRUBS AND GRASSES 3-5 Gal. 24" Ht. Min. 82

Aronia melanocarpa 'Morton' TM / Iroquis Beauty Black Chokeberry Buxus x 'Green Velvet' / Boxwood ostis x acutiflora `Karl Foerster` / Feather Read Gran Cornus stolonifera 'Arctic Fire' / Arctic Fire Dogwood Hypericum frondosum 'Sunburst' / Sunburst Hypericum Itea virginica 'Henry's Garnet' / Henry's Garnet Sweetspire Juniperus chinensis 'Gold Lace' / Gold Lace Juniper Juniperus horizontalis "Hughes" / Hughes Juniper Juniperus scopulorum 'Skyrocket' / Skyrocket Juniper Miscanthus sinensis 'Gracillimus' / Maiden Grass Miscanthus sinensis 'Morning Light' / Eulalia Grass Panicum virgatum 'Haense Herms' / Haense Herms Switch Grass

48.552 s

GENERAL LANDSCAPE REQUIREMENTS

- TREES MUST NOT BE PLACED WITHIN UTILITY EASEMENTS, BUT WITHIN ADJACENT AREAS THAT DO NOT CONFLICT WITH SUCH PUBLIC EASEMENTS AND MEET SITE LANDSCAPING REQUIREMENTS.
- THE DEVELOPER, ITS SUCCESSOR, AND/OR SUBSEQUENT OWNERS AND THEIR AGENTS WILL MAINTAIN LANDSCAPING ON THE PROPERTY ON A CONTINUING BASIS FOR THE LIFE OF THE DEVELOPMENT
- PLANT MATERIALS WHICH EXHIBIT EVIDENCE OF INSECT PESTS, DISEASE, AND/OR DAMAGE MUST BE APPROPRIATELY TREATED. DEAD PLANTS MUST BE
- 4. ALL LANDSCAPING IS SUBJECT TO PERIODIC INSPECTION BY THE PLANNING OFFICIAL OR DESIGNEE

206 E LLC

- THE PROPERTY OWNER WILL MAINTAIN LANDSCAPE AREAS IN GOOD CONDITION AND IN A WAY THAT PRESENTS A HEALTHY, NEAT, AND ORDERLY APPEARANCE. THIS MAINTENANCE MUST INCLUDE WEEDING, WATERING, FERTILIZING, PRUNING, MOWING, EDGING, MULCHING, OR OTHER MAINTENANCE IN ACCORDANCE WITH ACCEPTABLE HORTICULTURAL PRACTICES.
- THE CITY MAY CAUSE REMOVAL OF ANY DEAD OR DISEASED TREES. PLANTS, AND SHRUBS ON PRIVATE PROPERTY WITHIN THE CITY, WHEN THOSE TREES. PLANTS, AND SHRUBS CONSTITUTE A HAZARD TO LIFE AND/OR PROPERTY OR HARBOR INSECTS OR DISEASE WHICH CONSTITUTES A POTENTIAL THREAT TO OTHER TREES, PLANTS, OR SHRUBS WITHIN THE CITY.
- 7. NO TREE, SHRUB, OR WOODY VEGETATION WILL BE PLANTED WITHIN A DISTANCE OF 10 FEET FROM ANY FIRE HYDRANT OR FIRE DEPARTMENT CONNECTION (FDC) TO THE SPRINKLER SYSTEM.
- 8 NO TREES MAY BE PLANTED WITHIN 15 FEET OF A STREET LIGHT.
- ALL EXTERIOR-MOUNTED AND ALL ROOFTOP BUILDING HVAC AND MECHANICAL EQUIPMENT, VENTS, PIPING, ROOF ACCESS LADDERS, AND UTILITY METERS MUST BE LOCATED OUT OF VIEW OR OTHERWISE SCREENED FROM PUBLIC VIEW FROM ALL ADJACENT STREETS, SCREENING MUST BE ACCOMPLISHED WITH LANDSCAPING, SCREEN WALLS, BUILDING ELEMENTS, OR A COMBINATION OF THESE METHODS.
- 10. EXTERIOR GROUND-MOUNTED OR BUILDING-MOUNTED EQUIPMENT INCLUDING, BUT NOT LIMITED TO, MECHANICAL EQUIPMENT, UTILITIES' METER BANKS AND COOLERS MUST BE SCREENED FROM PUBLIC VIEW WITH THREE SIDED LANDSCAPING OR WITH AN ARCHITECTURAL TREATMENT COMPATIBLE WITH THE
- 11. ALL NEW ON-SITE WIRING AND CABLES MUST BE PLACED UNDERGROUND.
- 12. ANY LANDSCAPE MATERIAL TO BE USED FOR SCREENING MUST BE AT LEAST THE HEIGHT OF THE MATERIAL THAT IT IS INTENDED TO SCREEN.

10 S87°21'43"W 140.95' LANDSCAPE NOTES

Proposed Restaurant

RE: Arch

- 146 O'

Proposed Retail Building

RF: Arch

TRASH

LOCATE UTILITIES PRIOR TO COMMENCING LANDSCAPE OPERATIONS. ALL TREES SHALL BE FIELD POSITIONED AS TO AVOID CONFLICTS WITH EXISTING AND PROPOSED LITH ITIES. NOTIFY LANDSCAPE ARCHITECT OF ANY CONFLICTS OR OBSTRUCTIONS.

1"=30

2. CONTRACTOR SHALL STAKE ALL PLANTING AREAS IN THE FIELD PRIOR TO PLANTING FOR APPROVAL OF THE OWNER OR THEIR REPRESENTATIVE.

Turfgrass shall extend to

Imits of disturbance - TYP.

-a. RE: Landscape Note #32

- 3. OLIANTITIES SHOWN ARE FOR REFERENCE ONLY. CONTRACTOR SHALL VERIEVALL PLANT OLIANTITIES PRIOR TO RIDDING AND SHALL BE RESPONSIBLE FOR ALL QUANTITIES FOR THEIR BID. ANY DISCREPANCIES WITH THE PLAN SHALL BE BROUGHT TO THE ATTENTION OF THE LANDSCAPE ARCHITECT. THE PLAN QUANTITIES SHALL SUPERCEDE SCHEDULED QUANTITIES.
- 4. PLANT SYMBOLS ON LANDSCAPE PLAN ARE SHOWN AT FULL MATURE SIZE. ACTUAL PLANT SIZES AT INSTALLATION MY BE SMALLER AND SHALL BE THE MINIMUM PLANTING SIZE SPECIFIED IN PLANT SCHEDULE.
- ALL PLANT MATERIAL SHALL BE SPECIMEN QUALITY AND SHALL COMPLY WITH RECOMMENDATIONS AND REQUIREMENTS OF ANSI Z60.1 THE 'AMERICAN STANDARD FOR NURSERY STOCK
- 6. ALL PLANTING BEDS & NATIVE GRASS STANDS SHALL BE EDGED AS SHOWN IN PLAN.

V-Cut Edging Landscape Beds - TYP

RE: Landscape Detail

- PREPARE PLANTING BEDS AND INCORPORATE AMENDMENTS ACCORDING TO PLANS.
- SHREDDED HARDWOOD MULCH, PER SPECIFICATIONS SHALL BE USED AS A THREE INCH (3") TOP DRESSING IN ALL PLANTING BEDS AND AROUND ALL TREES SINGLE TREES AND SHRUBS SHALL BE MULCHED TO THE OUTSIDE EDGE OF THE SAUCER OR LANDSCAPE ISLAND.
- 9. ALL TREES SHALL BE STAKED PER DETAIL.
- 10. ALL PLANT MATERIAL SHALL BE INSTALLED TO ALLOW A ONE FOOT (1) CLEARANCE BETWEEN PLANT AND ADJACENT PAVEMENT.
- 11. THE LANDSCAPE CONTRACTOR SHALL NOT COMMENCE WORK UNTIL THE SITE IS FREE OF DEBRIS CAUSED BY ON-GOING CONSTRUCTION OPERATIONS. REMOVAL OF DERRIS SHALL BE THE RESPONSIBILITY OF THE GENERAL CONTRACTOR. LANDSCAPE WORK SHALL NOT REGIN LINTIL THE LANDSCAPE ARCHITECT AND OWNER HAVE GIVEN WRITTEN APPROVAL FOR SUCH. THERE SHALL BE NO DELAYS DUE TO LACK OF COORDINATION FOR THIS ACTIVITY.
- 12. THE LANDSCAPE ARCHITECT AND OWNER SHALL APPROVE GRADES AND CONDITION OF SITE PRIOR TO SODDING/SEEDING OPERATIONS
- 13. ALL AREAS DISTURBED DURING CONSTRUCTION AND NOT DESIGNATED FOR OTHER PLANTINGS OR HARDSCAPE SHALL BE SODDED WITH TURF TYPE FESCUE.
- 14 ALL LANDSCAPE AREAS SHALL BE IRRIGATED TURE AREAS SHALL BE IRRIGATED BY SPRAY OR ROTOR PLANT BEDS SHALL BE IRRIGATED BY DRIP IRRIGATION IRRIGATION SYSTEM SHALL INCLUDE AUTOMATIC RAIN-SENSOR DEVICE. IRRIGATION SHOP DRAWINGS SHALL BE PROVIDED BY THE CONTRACTOR FOR APPROVAL PRIOR TO CONSTRUCTION.
- 15 ALL DECORATIVE GRAVEL SHALL BE INSTALLED OVER GEOTEXTILE FARRIC (MIRAEL 140N OR APPROVED FOLIAL)

Ret 24-0155 Ridgeview hnson Coun Preliminary ∞ 듯

Δ=6°31'47" R=432.76" -40 32' (M) 40 33' (P

Sheet






UNDISTURBED SOIL WITH ROOT FLARE EVEN WITH OR 1" ABOVE GRADE. SCARIFY SIDES AND BOTTOM OF PIT. AMEND SOIL ACCORDING TO SPECIFICATIONS. DECIDUOUS TREE PLANTING DETAIL - NTS

Sheet

SHRUB PLANTING DETAIL - NTS

- CONTRACTOR SHALL LOCATE AND MARK ALL PLANTBED
 LOCATIONS PRIOR TO EXCAVATING FOR FINAL APPROVAL BY OWNER OR LANDSCAPE ARCHITECT.
 TRANSITION TO MULCH CONTAINMENT DETAIL AT ALL
- LOCATIONS ADJACENT TO CURBS & SIDEWALKS. RE: DETAIL,
- THIS SHEET.
 CONTRACTOR TO VERIFY ALL UTILITY LOCATIONS PRIOR TO TRENCHING OR LANDSCAPE INSTALLATION.





 TREES THAT DO NOT MEET THE SIZE REQUIREMENT WILL BE REJECTED. TREES SHALL BE INSPECTED BY OWNERS REPRESENTATIVE PRIOR TO INSTALLATION.

3 x ROOT BALL DIA

SECTION









UTILITY BOXES SHALL BE CLUSTERED AS MUCH AS POSSIBLE

TYPICAL UTILITY BOX SCREENING DETAILS - NTS

PRUNE OUT ANY DEAD OR BROKEN BRANCHES AND REMOVE DEBRIS FROM SITE.

MOVEMENT OF THE TRUNK WITH THE WIND

MIN. 6' LONG STEEL STAKES SECURED

RING TO CREATE A SAUCER FORM.

BALL AND TRUNK. PEEL AND REMOVE

REMOVE TWINE AND CAGE FROM ROOT

BURLAP FROM TOP 1/3 OF THE ROOT BALL.

BUT NO DEEPER PLACE BOOT BALL ON

PLANTING HOLE SHALL BE AT LEAST 3 TIMES WIDER THAN THE SPREAD OF ITS ROOTS,

AND SOUTH OF TREE.

INTO UNDISTURBED SOIL. PLACE NORTH

SECURE TREE TO STAKES WITH STRAPS (RE: SPECS).

STRAPS SHALL BE LOOSE ENOUGH TO ALLOW SOME

SET TREE WITH TOP OF ROOT BALL FLUSH WITH GRADE.

BALL. REMOVE EXCESS SOIL TO TOP OF LATERAL ROOTS.

3" MULCH PER SPECIFICATIONS. DO NOT PLACE ON

TRUNK OR TRUNK FLARE. BERM AT OUTER EDGES OF


TRUNK FLARE MUST BE VISIBLE AT THE TOP OF ROOT

GEOTEXTILE FABRIC AS SECTION EDGES UP AT CORNERS

NOTES

- SET ALL EDGING 1" ABOVE FINISH GRADE AS SHOWN.
- EDGING SHALL ABUT ALL CONCRETE CURBS AND WALKS PERPENDICULAR AND FLUSH WITH TOP OF CONCRETE ALL JOINTS SHALL BE SECURELY STAKED
- CONTRACTOR SHALL CUT TOP EDGES AS NEEDED TO BE PARALLEL WITH GRADE. ALL GRAVEL SHALL BE INSTALLED OVER A GEOTEXTILE FABRIC
- (MIRAFI 140N OR APPROVED EQUAL). GRAVEL SHALL BE APPROVED BY OWNER PRIOR TO INSTALLATION. FILTER FABRIC SHALL NOT BE VISIBLE AFTER GRAVEL INSTALLATION.

MOW EDGE DETAIL - NTS



MULCH CONTAINMENT DETAIL - NTS

HARDWOOD MULCH

AS SPECIFIED

TRENCH EDGE AROUND

PLANTING BEDS;

HARDWOOD MULCH

SIDEWALK OR

HARDSCAPE

SURFACE

BACKFILL WITH

AS SPECIFIED

PLANTING POCKET

3" HARDWOOD MULCH

- AMENDED PLANTING

SOIL MIX ACCORDING

- LANDSCAPING; RE: PLAN

CONTAINER PLANTING DETAIL - NTS

PRUNE OUT ANY DEAD OR BROKEN BRANCHES. CUT ANY GIRDLING ROOTS - INSTALL 3" OF HARDWOOD MULCH THROUGHOUT PLANTING OFF CLOSE TO THE CROWN. PRY LONG ROOTS OUT TO DIRECT INTO NEW SOIL BED. LEAVE A 6" BARE CIRCLE AT BASE OF PLANT PLACE SHRUB SO CROWN IS AT SOIL LEVEL PROVIDE MULCH - FILL PLANTING HOLE WITH AMENDED SOIL MIX ACCORDING TO SPECIFICATIONS. CONSTRUCT RING ADJACENT TO HARDSCAPE; RE: DETAIL AROUND PLANTED SHRUB TO FORM CURB, WHERE APPLICABLE; SAUCER MAINTAIN A MINIMUM OF 4' TO CENTER OF ROOTBALL FROM BACK OF CURB BOTTOM (MIN 6") NOTES

- LARGER THAN 4' MATURE DIAMETER, PROVIDE A GREATER OFFSET EQUAL TO 1/2 OF THE MATURE DIAMETER MINIMUM

REFER TO SPECIFICATIONS FOR TOPSOIL BACKFILL MIX.

CONTRACTOR TO WATER THOROUGHLY AFTER PLANTING INSTALLATION TO BE IN ACCORDANCE WITH PLANTING SPECIFICATIONS

WHERE ADJACENT TO CURB, MAINTAIN THE MINIMUM OFFSET SHOWN. FOR SHRUBS